



Lighthouse
ADHESIVES

Cove GLU
UNIVERSAL COVE BASE ADHESIVE



DESCRIPTION


Cove GLU is a very aggressive premium adhesive engineered with outstanding wet grab for the installation of a wide variety cove base. Cove GLU is solvent free and offers excellent performance characteristics complementing its strong and durable bond for challenging installations.



Approved Floor Covering

- Vinyl Cove Base (PVC)
- Rubber Cove Base

Required Applications & Coverage

FLOOR COVERING	TROWEL RECOMMENDATION	ESTIMATED COVERAGE
Cove Base	1/8" x 1/8" x 1/8" Saw Notch 	Up to 180 lf/gallon
3 Hole Applicator		Up to 60 lf/per tube

DISCLAIMER: Users should determine the suitability of this information and product for their own purpose or application. The manufacturer is not responsible for the misuse of this product. This adhesive is only warranted to maintain an adhesive bond when used as prescribed by Lighthouse Adhesives.



1-844-GLURU-4U



LIGHTHOUSE ADHESIVES

4284 South Dixie Hwy
Resaca GA 30735
lighthouseadhesives.com

Limitations

- Not for exterior installations
- Not for use to encapsulate asbestos
- Ambient conditions must be between 50°-100° F - 20-75% RH
- Extreme ambient condition changes will affect the performance quality of the installation
- Do not install over chemically treated walls
- Do not allow product to freeze
- Do not use with dimensionally unstable wall base

Suitable Substrates

- Plywood/OSB
- Plaster
- Gypsum drywall
- Concrete
- Concrete Block
- Cement backer board
- Brick

PLEASE CONSULT LIGHTHOUSE ADHESIVES' TECHNICAL DEPARTMENT FOR SUBSTRATES NOT LISTED

Surface Preparation

NOTE: FOLLOW ALL COVE BASE MANUFACTURERS GUIDELINES AS WELL AS THE FOLLOWING:

- Wall must be dry, smooth, solid, structurally sound.
- Wall should be clean and free of dust, dirt, oil, grease, loosely bonded toppings, loose particles, and any other substance or condition that may prevent or reduce adhesion.
- Wall, adhesive and cove base must be acclimated with HVAC in operation for 48 hours prior, during, and continuously after installation is complete.
- Ambient temperature must be between 50°-100° F and relative humidity must be between 20-75% during and following wall base installation.

Installation Instructions

Follow cove base manufacturer's guidelines for layout, design and any special precautions for installation.

DISCLAIMER: FOLLOW THESE INSTRUCTIONS COMPLETELY OR DO NOT USE THIS PRODUCT.

- 1) *** If unfamiliar with a product, always perform a bond test. Spread a small area of adhesive and install the desired product into the adhesive to ensure the proper bond is achieved. ***
- 2) After surface preparation, spread adhesive using the determined trowel as needed for desired product type.

After spreading the adhesive on the wall or cove base backing using the recommended application method, place base into the desired position on the wall and roll with a handheld roller.

Cleanup

- While wet, use a cloth and soapy water to remove wet adhesive
- When adhesive is dry, use denatured alcohol or appropriate adhesive remover
- Always check for compatibility on a piece of scrap product.

Storage

- This product should be stored at temperatures between 50°-90° degrees F.
- This product has a shelf life of 2 years

LIGHTHOUSE ADHESIVES

4284 South Dixie Hwy
Resaca GA 30735
lighthouseadhesives.com



1-844-GLURU-4U